



# TJ Lower A-Pillar Light Mounts

**IMPORTANT:** Thank you for purchasing this Poison Spyder product. Please read through this entire document before proceeding with installation. If you are not confident in your mechanical skills, please seek the help of a professional to perform the installation. Check your packages immediately upon arrival to ensure that everything listed is included, and to check for damage during shipping. If anything is missing or damaged, or if you need technical assistance with any aspect of this installation, call Poison Spyder at (951) 849-5911 as soon as possible. This document last updated May 2015.

## APPLICATIONS

These installation instructions apply to the following Poison Spyder products:



**45-28-RDA2** TJ Lower A-Pillar Light Mounts

## PARTS LIST

Please check your packages immediately upon arrival to ensure that everything listed is included, and to check for damage during shipping. If anything is missing or damaged, call Poison Spyder at (951) 849-5911 as soon as possible.

- (1) Driver Side JK Lower A-Pillar Light Mount
- (1) Passenger Side TJ Lower A-Pillar Light Mount
- (2) TJ Lower A-Pillar Light Mount Rubber Liners
- (1) TJ Lower A-Pillar Light Mount Hardware Kit
  - PN: 45-28-RDA2 includes:
  - (4) 5/16-18 X 1 SS Button Head Cap Screw
  - (4) 5/16 SAE Hardened Flat Washer

## INSTALLATION NOTES

- **This product is designed primarily** for mounting the Rigid Industries Dually or Dually D2 LED lights. No guarantee is made regarding fitment of other brands of off-road or auxiliary lights, however it will likely work with most

lights that are in a compact housing. The light mounting hole is 7/16".

- **Remove the two bolts on** the front-ward side of the windshield brace on the lower A-Pillar
- **Place the rubber liners between** the mount and the lower A-pillar, to protect the Jeep's paint.
- **If installing the Lower A-Pillar** light mounts in conjunction with Poison Spyder's A-Pillar Light Bar Mounts, the provided stainless steel button head cap screws will be necessary, as the stock hardware is too short when stacking both brackets. If installing the Lower A-Pillar Light Mounts by themselves, use of the provide stainless steel button head cap screws is optional.

